

## Anti-slip spray 303

Creates non-slip floors with safety



### Material description



<b>Material type:</b>	Colorless acrylic-based coating for interior use.	
<b>Intended use:</b>	Anti-Slip Spray 303 is the quick solution for more slip resistance and therefore more safety eit. In the bathroom, in the shower tray and wherever there is a risk of slipping. Easy to use on surfaces such as tiles, ceramics, natural stone, sanitary acrylic, gelcoat, enamel. For indoor and outdoor use.	
<b>Properties:</b>	<ul style="list-style-type: none"> <li>• Transparent</li> <li>• quick drying</li> <li>• UV-resistant</li> <li>• Easy to process</li> <li>• Easy to clean surface</li> <li>• Slip resistance R10 (DIN 51130)</li> <li>• Slip resistance class B (DIN 51097)</li> </ul>	
<b>Color shades:</b>	<b>Order no:</b> 303 0000	<b>Color shade:</b> colorless, transparent
<b>Packaging:</b>	400 ml spray can	
<b>Storage:</b>	Store in a cool, dry place in a tightly closed original container. Official regulations must be observed.	

### Technical application notes

<b>Substrates:</b>	Tiles, ceramics, natural stone, sanitary acrylic, gelcoat, enamel
<b>Substrate preparation:</b>	The substrate must be dry, clean and sound.
<b>Coating structure:</b>	4 x Anti-slip spray 303 in the cross walk
<b>Processing conditions:</b>	<p>Shake spray can well before use.</p> <p>During the entire processing and drying time, the material, substrate and air temperature must not fall below 8°C and not exceed 30°C. The air humidity should be between 30% RH and 75% RH during the entire time.</p>
<b>Tool cleaning:</b>	With special thinner 44 immediately after finishing work.

---

## Labeling

---

<b>Declaration of ingredients:</b>	Acrylic resin, organic solvents, additives		
<b>Waste code:</b>	080111	<b>Giscode:</b>	No classification
<b>Disposal:</b>	Only dispose of completely empty containers for recycling.		
<b>Other:</b>	The accident prevention regulations of BG Chemie "Processing of coating materials" (VBG 23), the leaflet "Solvents" (M 017) and the "Technical Rules for Hazardous Substances (TRGS) 507" must be observed. Remove food from the relevant rooms during processing and the drying time. Further information can be found in the EC safety data sheet.		

---

## Processing instructions

---

Drying / recoatability	non-slip	dry
(20°C/55% r.h.) *	~ 15 min	24 hrs.
<b>Yield</b>	~ 1.5 m <sup>2</sup> / can	

---

## Special notes

---

\* Specified drying times apply at 20°C / 55% relative humidity and sufficient air movement.

The following conditions may delay drying:

- **Low temperatures**
- **High humidity**
- **Excessive layer thickness**
- **Lack of air movement**

### Status 01/20

PAUL JAEGER GMBH & CO. KG • Siemensstrasse 6 • 71696 Möglingen • Phone +49 7141-24 44-0 • Fax +49 7141-24 44 55 • info@jaegerlacke.de • [www.jaegerlacke.de](http://www.jaegerlacke.de)

Our written and verbal application recommendations, which we provide to support the processor on the basis of our practical experience and to the best of our knowledge in accordance with the current state of science and technology, are non-binding and do not constitute a contractual legal relationship or an ancillary obligation arising from the purchase contract. They do not release the buyer from the obligation to check the suitability of the products for the intended use on his own responsibility. In the event of the publication of a new edition due to technical progress, the above information shall lose its validity. In all other respects, our General Terms and Conditions apply.