Jaeger Iso-Mineral Primer 309

White plaster primer for indoors and outdoors

Material description

Material type:
Jaeger Iso-Mineralgrund consists of a water-dilutable polymer resin, a specially formulated pigment-filler mixture and adhesion-enhancing additives.

Intended use:
Jaeger Iso-Mineral Primer is a universal plaster primer for all decorative painting techniques with mineral fillers and plasters, for exterior and interior use. Especially for substrate preparation for Jaeger Antiqua, Epoca Marble, Stucco Fondo, Stucco Romano and Fresco Veneziano. Jaeger Iso-Mineral Primer improves adhesion and facilitates the application of an even layer of filler in exterior and interior areas.

Properties:
Jaeger Iso-Mineral Primer is a hard-elastic coating that is also effective against the penetration of dirt from the substrate, especially wood constituents.

- water-dilutable
- environmentally friendly

Color shades:

Order no:	**Color shade:**
309 0800	white

Gloss level: dull

Yield: 4 - 6 m" / kg

Density: approx. 1.48 g / cm3 at 20°C

Packaging: 5 kg 25 kg

Dilution: Water, max. 5%

Storage:
Shelf life is at least 1 year if stored in a cool, dry place in a tightly closed original container. Protect from frost.

Technical application notes

Working method:

1. substrate pre-treatment
The substrate should be dry, clean and stable. Prime highly absorbent substrates with Kronen® Hydrosol Deep Primer 307.

2. apply:
Apply 1x Jaeger Iso-Mineralgrund undiluted.

Processing conditions:
During the entire application and drying time, the material, substrate and air temperature must not fall below 8°C and not exceed 30°C. The air humidity should be between 30% RH and 75% RH during the entire time.

Tool cleaning:
Clean with water immediately after use.

Labeling

Declaration of ingredients:	Acrylic dispersion, water, pigments, mineral fillers, additives, pot preservative
Waste code:	080111
Disposal:	Only dispose of completely empty containers for recycling. Hardened residues can be disposed of with the residual waste. Liquid paint residues must be disposed of via the hazardous waste collection points or approved disposal companies.
Other:	The accident prevention regulations of BG Chemie "Processing of coating materials (VBG 23), the information sheet "Solvents" (M 017) and the "Technical Rules for Hazardous Substances (TRGS) 507" must be observed. Remove food from the relevant rooms during processing and the drying time. Further information can be found in the EC safety data sheet.

Processing instructions

Application method	**paint / roll**		
Dilution (water)	undiluted		
Consumption	0.2 kg/m²	depending on the roughness of the substrate	

Drying	**Dust-dry**	**reworkable**	
(20°C/55% r.h.)	approx. 30 - 60 min.	approx. 2 hrs.	

Status 11/14
PAUL JAEGER GMBH & CO. KG• Siemensstrasse 6• 71696 Möglingen• Phone +49 7141-24 44-0• Fax +49 7141-24 44 55• info@jaegerlacke.de •www.jaegerlacke.de
Our written and verbal application recommendations, which we provide to support the processor on the basis of our practical experience and to the best of our knowledge in accordance with the current state of science and technology, are non-binding and do not constitute a contractual legal relationship or an ancillary obligation arising from the purchase contract. They do not release the purchaser from the obligation to check the suitability of the products for the intended purpose on his own responsibility. In the event of the publication of a new edition due to technical progress, the above information shall lose its validity. In all other respects, our General Terms and Conditions apply.