

Sabbia 929

Decorative pearl metallic finish



Material description



Material type:	Decorative top coat with a fine metallized sand grain structure on a water-based basis.	
Intended use:	Jaeger Sabbia is suitable for finishing all decorative surfaces in interiors. The structure of the surface can be individually designed using the brush strokes, resulting in an all-round brilliant look.	
Properties:	<ul style="list-style-type: none">• Brilliant surface• solvent-free• water-dilutable• Easy to process• produces interesting light and shadow effects	
Color shades:	Order no:	Color shade:
	929 0700	Gold
	929 0701	Silver
	929 0704	Copper
Gloss level:	Shiny	
Density:	approx. 1.27 g/ml	
Packaging:	1 ltr	
Dilution:	Water (adjusted ready for use)	
Storage:	Store in a cool, dry place in a tightly closed original container. Protect from heat, frost and direct sunlight. Can be stored for approx. 2 years in the unopened original container.	

Technical application notes

Substrates:	Old emulsion paints, mineral substrates, plasterboard, wallpaper, polystyrene, fiberboard, blockboard and other wood-based materials.
Substrate preparation:	Substrates must be clean, dry and sound. Loose parts must be removed.
Coating structure:	1x Jaeger Iso-Mineral Primer 309 1 - 2 x Jaeger Sabbia 929 Apply Jaeger Sabbia with a brush / paintbrush / roller in small sections without direction, then immediately structure the surface.
Processing conditions:	During the entire processing and drying time, the material, substrate and air temperature must not fall below 8°C and must not exceed 30°C. The air humidity should be between 30% RH and 80% RH during the entire time. High humidity and low temperatures delay the drying of the coating film.
Tool cleaning:	Wash immediately after use with plenty of soap and water.

Labeling

Waste code:	080112	Product code:	M-DF01
Disposal:	Only dispose of completely empty containers for recycling. Hardened residues can be disposed of with residual waste. Liquid paint residues must be disposed of via the hazardous waste collection points or authorized disposal companies.		
Note:	Keep out of the reach of children. Ensure thorough ventilation during processing and drying. Avoid eating, drinking and smoking while using the paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Clean tools immediately after use with soap and water.		
Other:	The accident prevention regulations of BG Chemie "Processing of coating materials" (VBG 23) must be observed. Remove foodstuffs from the relevant rooms during processing and the drying time. Further information can be found in the EC safety data sheet.		

Processing instructions

Application method	Painting / rolling	
Dilution	undiluted	
Drying	Dust-dry	Dried
(20°C/55% r.h.)	~ 30 min	~ 2 hours.
Yield	paint / roll	
m ² / ltr.	approx. 8	

Status 07/18

PAUL JAEGER GMBH & CO. KG • Siemensstrasse 6 • 71696 Möglingen • Phone +49 7141-24 44-0 • Fax +49 7141-24 44 55 • info@jaegerlacke.de • www.jaegerlacke.de

Our written and verbal application recommendations, which we provide to support the processor on the basis of our practical experience and to the best of our knowledge in accordance with the current state of science and technology, are non-binding and do not constitute a contractual legal relationship or an ancillary obligation arising from the purchase contract. They do not release the purchaser from the obligation to test products for their suitability for the intended purpose on his own responsibility. In the event of the publication of a new edition due to technical progress, the above information shall lose its validity. In all other respects, our General Terms and Conditions apply.