


992

# Vulcano

For textured surfaces with a lava stone look

## Material description

**Material type:** Vulcano consists of a high-quality siloxane binder and mineral fillers.

**Intended use:** For high-profile exterior and interior surfaces that can be individually finished using textured rollers and a Venetian trowel. Vulcano Finish is applied as a coloured top coat using a glazing brush or sponge.

**Properties:**

+ Extremely durable siloxane binder
+ Allows water vapour to diffuse
+ Alkali-resistant
+ Suitable for coating concrete surfaces and lime plaster
+ Highly abrasion-resistant
+ weather-resistant
+ good UV resistance
+ for indoor and outdoor use
+ Available with sophisticated glitter particles on request (991 Diamond Effect)

**Colours:**

**Item no./ Colour**

992-0800 white
992-9005 black

**Coverage:** 1.5–2 kg/m² per coat, depending on coat thickness

**Density:** 1.81 g/cm³ at 20°C

**Packaging:** 20 kg

**Grain size:** 0.5 mm

**Dilution:** ready for use

**Storage:** Store in a cool, dry place in the original, tightly sealed container. Comply with regulatory requirements. Protect from frost.

## Application instructions

**Method of application:**

1. Surface preparation: Clean the surface thoroughly and remove any loose particles. Prime highly absorbent substrates with a deep-penetrating primer.

Prime surfaces (exterior and interior) with Iso-Mineralgrund 309.

| | |
|---|---|
| 2. Filling: | Apply Jaeger Vulcano in 1–2 coats using the 974 finishing trowel and create texture using a textured roller or the finishing trowel.<br>For the typical Vulcano finish, apply one coat of Vulcano thickly. A 4 mm notched trowel or finishing trowel is suitable for this. After allowing the surface to set for 15–30 minutes, work the surface with a textured roller. After a further 15–30 minutes, smooth lightly with a clean Venetian trowel and texture as desired. The longer the drying time, the more intense and coarse the textures will be. |
| 3. Surface finish: | After a drying time of 12 hours, Jaeger Vulcano is coated with 1–2 coats of Vulcano Finish using a glazing brush or sponge.<br>The Vulcano Finish is individually coloured for this purpose using mineral paint concentrate. |
| **Application conditions:** | Throughout the entire application and drying period, the temperature of the material, substrate and air must not fall below 8°C or exceed 30°C. The relative humidity should remain between 30% RH and 75% RH throughout this period. |
| **Tool cleaning:** | Clean with water immediately after use. |

## Labelling

| | | | |
|---|---|---|---|
| **Waste code:** | 080111 | **Giscode:** | No classification |
| **Disposal:** | Only send completely empty containers for recycling. Hardened residues may be disposed of with general waste. Liquid paint residues must be disposed of via hazardous waste collection points or authorised waste management companies. | | |
| **Other:** | The accident prevention regulations of the BG Chemie 'Processing of Coating Materials (VBG 23)', the information sheet 'Solvents' (M 017) and the 'Technical Rules for Hazardous Substances (TRGS) 507' must be observed.<br>Remove food from the relevant rooms during application and the drying period.<br>Further information can be found in the EC Safety Data Sheet. | | |

**As at 26 February**
PAUL JAEGER GMBH & CO. KG• Siemensstraße 6• 71696 Möglingen• Telephone +49 7141-24 44-0• Fax +49 7141-24 44 55• info@jaegerlacke.de• www.jaegerlacke.de
Our technical application recommendations, whether verbal or in writing, which we provide to assist the user based on our practical experience, to the best of our knowledge and in accordance with the current state of science and technology, are non-binding and do not constitute a contractual legal relationship or any ancillary obligation arising from the sales contract. They do not relieve the purchaser of the responsibility to test the products themselves to ensure their suitability for the intended purpose. Should a new edition be published as a result of technical progress, the above information shall cease to be valid. In all other respects, our General Terms and Conditions apply.

**You can access detailed product information directly via the product page:**
**https://www.jaegerlacke.de/produkte-loesungen/spachteltechniken-villa-venezia/vulcano-992**