

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Sinolin Heizkörperlackspray  
Revision date : 27.07.2016  
Print date : 04.07.2018

Version (Revision) : 3.0.0 (2.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Sinolin Heizkörperlackspray (2780000)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Coating product to be used by professional / private user. For further information please refer to the technical data sheet.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier (manufacturer/importer/only representative/downstream user/distributor)

Paul Jaeger GmbH & Co KG

Street : Siemensstr. 6

Postal code/city : 71696 Möglingen

Telephone : 07141 / 2444-0

Telefax : 07141 / 2444-44

Information contact : info@jaegerlacke.de

### 1.4 Emergency telephone number

Vergiftungs-Informations-Zentrale Freiburg Tel. 0761/ 19240

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2A ; Causes serious eye irritation.

Aerosol 1 ; H222 - Flammable aerosols : Category 1 ; Extremely flammable aerosol.

Aerosol 1 ; H229 - Flammable aerosols : Category 1 ; Pressurised container: May burst if heated.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02) · Exclamation mark (GHS07)

##### Signal word

Danger

##### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

##### Precautionary statements

P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Sinolin Heizkörperlackspray  
**Revision date :** 27.07.2016  
**Print date :** 04.07.2018

**Version (Revision) :** 3.0.0 (2.0.0)

P211 Do not spray on an open flame or other ignition source.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/container to disposal

### Special rules for supplemental label elements for certain mixtures

EUH208 Contains 2-BUTANONE OXIME. May produce an allergic reaction.

## 2.3 Other hazards

None

## SECTION 3: Composition / information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

ACETONE ; REACH registration No. : 01-2119471330-49 ; EC No. : 200-662-2; CAS No. : 67-64-1

Weight fraction : 20 - 25 %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; REACH registration No. : 01-2119463258-33-XXXX ; EC No. : 265-150-3; CAS No. : 64742-48-9

Weight fraction : 10 - 20 %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336

HYDROCARBONS, C9-C12, N-ALKANES, CYCLOALANES, ISOALKANES AROMATICS (2-25%) ; REACH registration No. : 01-2119458049-33 ; EC No. : 919-446-0

Weight fraction : 2,5 - 10 %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304

2-BUTANONE OXIME ; EC No. : 202-496-6; CAS No. : 96-29-7

Weight fraction : 0,1 - 0,5 %

Classification 1272/2008 [CLP] : Carc. 2 ; H351 Eye Dam. 1 ; H318 Acute Tox. 4 ; H312 Skin Sens. 1 ; H317

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

#### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Sinolin Heizkörperlackspray  
Revision date : 27.07.2016  
Print date : 04.07.2018

Version (Revision) : 3.0.0 (2.0.0)

No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO<sub>2</sub>) Water mist Extinguishing powder

##### Unsuitable extinguishing media

Full water jet

#### 5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Do not inhale explosion and combustion gases. Use suitable breathing apparatus.

##### Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO<sub>x</sub>) Carbon monoxide. Carbon dioxide (CO<sub>2</sub>) Hydrocarbons

#### 5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Clear spills immediately.

##### For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

##### For cleaning up

Clean with detergents. Avoid solvent cleaners.

#### 6.4 Reference to other sections

None

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Protective measures

###### Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use only antistatically equipped (spark-free) tools. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Electrical equipment should be protected to the appropriate standard.

###### Environmental precautions

Shafts and sewers must be protected from entry of the product.

###### Specific requirements or handling rules

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Sinolin Heizkörperlackspray  
**Revision date :** 27.07.2016  
**Print date :** 04.07.2018

**Version (Revision) :** 3.0.0 (2.0.0)

Inhalation of dust/particles Skin contact Eye contact Never use pressure to empty container. Wear personal protection equipment (refer to section 8).

#### Additional information

Keep/Store only in original container. Comply with the health and safety at work laws. Do not allow to enter into surface water or drains.

### 7.2 Conditions for safe storage, including any incompatibilities

To follow : Betriebs-sicherheitsverordnung (BetrSichV)

#### Hints on joint storage

##### Materials to avoid

Strong acid Strong alkali Oxidising agent

#### Further information on storage conditions

See information supplied by the manufacturer. Keep/Store only in original container. Store in a place accessible by authorized persons only. Keep away from sources of ignition. - No smoking. Keep container tightly closed. Always close containers tightly after the removal of product.

**Storage temperature :** of °C up to °C

### 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

ACETONE ; CAS No. : 67-64-1

Limit value type (country of origin) : TWA ( EC )

Limit value : 500 ppm / 1210 mg/m<sup>3</sup>

Version : 08.06.2000

### 8.2 Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Personal protection equipment

##### Eye/face protection

###### Suitable eye protection

Eye glasses with side protection

##### Skin protection

###### Hand protection

**Suitable material :** FKM (fluoro rubber)

**Required properties :** liquid-tight.

**Breakthrough time (maximum wearing time) :** > 10 min See information supplied by the manufacturer.

**Thickness of the glove material :** 0,5mm

**Recommended glove articles :** When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

**Additional hand protection measures :** Check leak tightness/impermeability prior to use. Do not wear gloves near rotary machines and tools. Take recovery periods for skin regeneration. In the case of wanting to use the gloves again, clean them before taking off and air them well.

**Remark :** For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

###### Body protection

**Required properties :** antistatic.

**Recommended material :** Natural fibres (e.g. cotton) heat-resistant synthetic fibres

#### Respiratory protection

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Sinolin Heizkörperlackspray  
Revision date : 27.07.2016  
Print date : 04.07.2018

Version (Revision) : 3.0.0 (2.0.0)

Respiratory protection necessary at: exceeding exposure limit values

### Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter: A

### Consumer exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state : Aerosol

Colour : please refer to label

#### Odour

like: Solvents/Thinner

#### Safety relevant basis data

Initial boiling point and boiling range :	( 1013 hPa )	not applicable	
Flash point :		not applicable	
Lower explosion limit :		0,7	Vol-%
Upper explosion limit :		32	Vol-%
Flow time :	( 20 °C )	not applicable	DIN-cup 4 mm

### 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions(See section 7).

### 10.3 Possibility of hazardous reactions

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

### 10.5 Incompatible materials

No information available.

### 10.6 Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours. Exothermal decomposition with formation of: Carbon dioxide. Carbon monoxide. Nitrogen oxides (NOx). carbon black.

## SECTION 11: Toxicological information

There are no data available on the preparation/mixture itself. Classification according to Regulation (EC) No. 1272/2008 [CLP] See Sections 2 and 3 for details.

### 11.1 Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Sinolin Heizkörperlackspray  
**Revision date :** 27.07.2016  
**Print date :** 04.07.2018

**Version (Revision) :** 3.0.0 (2.0.0)

allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## Acute effects

Acute toxicity No information available.

## Irritant and corrosive effects

Skin corrosion/irritation Serious eye damage/eye irritation No information available.

## Sensitisation

Respiratory or skin sensitisation No information available.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

### Carcinogenicity

No information available.

### Germ cell mutagenicity

No information available.

### Reproductive toxicity

No information available.

## STOT-single exposure

No information available.

## STOT-repeated exposure

No information available.

## Aspiration hazard

No information available.

## SECTION 12: Ecological information

There are no data available on the preparation/mixture itself. Do not allow to enter into surface water or drains.

### 12.1 Toxicity

No information available.

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

No information available.

### 12.6 Other adverse effects

No information available.

### 12.7 Additional ecotoxicological information

None

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Do not allow to enter into surface water or drains. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### Product/Packaging disposal

##### Waste codes/waste designations according to EWC/AVV

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Sinolin Heizkörperlackspray  
Revision date : 27.07.2016  
Print date : 04.07.2018

Version (Revision) : 3.0.0 (2.0.0)

## Other disposal recommendations

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

## SECTION 14: Transport information

### 14.1 UN number

UN 1950

### 14.2 UN proper shipping name

Land transport (ADR/RID)

AEROSOLS

Sea transport (IMDG)

AEROSOLS

Air transport (ICAO-TI / IATA-DGR)

AEROSOLS, FLAMMABLE

### 14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 2  
Classification code : 5F  
Hazard identification number (Kemler No.) : 23  
Tunnel restriction code : D  
Special provisions : LQ 2 · E 0  
Hazard label(s) : 2.1

Sea transport (IMDG)

Class(es) : 2.1  
EmS-No. : F-D / S-U  
Special provisions : LQ 11 · E 0  
Hazard label(s) : 2.1

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 2.1  
Special provisions : E 0  
Hazard label(s) : 2.1

### 14.4 Packing group

### 14.5 Environmental hazards

Land transport (ADR/RID) : No  
Sea transport (IMDG) : No  
Air transport (ICAO-TI / IATA-DGR) : No

### 14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None

### 15.2 Chemical Safety Assessment

No information available.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Sinolin Heizkörperlackspray  
**Revision date :** 27.07.2016  
**Print date :** 04.07.2018

**Version (Revision) :** 3.0.0 (2.0.0)

### SECTION 16: Other information

#### 16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling (67/548/EEC or 1999/45/EC) · 14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Sea transport (IMDG) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG) · 14. Transport hazard class(es) - Air transport (ICAO-TI / IATA-DGR)

#### 16.2 Abbreviations and acronyms

None

#### 16.3 Key literature references and sources for data

None

#### 16.4 Relevant H- and EUH-phrases (Number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

#### 16.5 Training advice

None

#### 16.6 Additional information

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.