Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

Trade name :	609 Konservierungslack-Spray alle Glanzgrade		
Revision date :	20.12.2023	**Version (Revision) :**	3.1.0 (3.0.0)
Print date :	20.12.2023		

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

609 Konservierungslack-Spray
alle Glanzgrade (6090001)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Coating product to be used by professional / private user. For further information please refer to the technical data sheet.

1.3 Details of the supplier of the safety data sheet

Supplier

Paul Jaeger GmbH & Co KG

Street : Siemensstr. 6

Postal code/City : 71696 Möglingen

Telephone : 07141 / 2444-0

Telefax : 07141 / 2444-44

Information contact : info@jaegerlacke.de

1.4 Emergency telephone number

Vergiftungs-Informations-Zentrale Freiburg Tel. 0761/ 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1 ; H229 - Aerosols : Category 1 ; Pressurised container: May burst if heated.

Aerosol 1 ; H222 - Aerosols : Category 1 ; Extremely flammable aerosol.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Flame (GHS02) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

ETHYL ACETATE ; CAS No. : 141-78-6

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to disposal of paints.

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

DIMETHYL ETHER ; EC No. : 204-065-8; CAS No. : 115-10-6

Weight fraction :	≥ 25 - < 50 %
Classification 1272/2008 [CLP] :	Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280 Substance with a community workplace exposure limit

ETHYL ACETATE ; REACH No. : 01-2119475103-46 ; EC No. : 205-500-4; CAS No. : 141-78-6

Weight fraction :	≥ 25 - < 50 %
Classification 1272/2008 [CLP] :	Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 EUH066

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5; CAS No. : 64742-95-6

Weight fraction :	≥ 10 - < 20 %
Classification 1272/2008 [CLP] :	Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411 EUH066

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction :	≥ 2,5 - < 10 %
Classification 1272/2008 [CLP] :	Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact
Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact
In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion
If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed
No information available.

4.3 Indication of any immediate medical attention and special treatment needed
None

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing media
alcohol resistant foam Carbon dioxide (CO2) Water mist Extinguishing powder

Unsuitable extinguishing media
Full water jet

5.2 Special hazards arising from the substance or mixture
Burning produces heavy smoke. Do not inhale explosion and combustion gases. Use suitable breathing apparatus.

Hazardous combustion products
In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide Carbon dioxide (CO2) Hydrocarbons

5.3 Advice for firefighters
Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

6.2 Environmental precautions
Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up
Clear spills immediately.

For containment
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up
Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections
None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use only antistatically equipped (spark-free) tools. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Electrical equipment should be protected to the appropriate standard.

Environmental precautions

Shafts and sewers must be protected from entry of the product.

Specific requirements or handling rules

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Inhalation of dust/particles Skin contact Eye contact Never use pressure to empty container. Wear personal protection equipment (refer to section 8).

Further information

Keep/Store only in original container. Comply with the health and safety at work laws. Do not allow to enter into surface water or drains.

7.2 Conditions for safe storage, including any incompatibilities

To follow : Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Materials to avoid

Strong acid Strong alkali Oxidizing agent

Further information on storage conditions

See information supplied by the manufacturer. Keep/Store only in original container. Store in a place accessible by authorized persons only. Keep away from sources of ignition - No smoking. Keep container tightly closed. Always close containers tightly after the removal of product. Keep in a cool, well-ventilated place. Protect against Heat. UV-radiation/sunlight

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

DIMETHYL ETHER ; CAS No. : 115-10-6

Limit value type (country of origin) :	TWA (EC)
Limit value :	1000 ppm / 1920 mg/m^3
Version :	20.06.2019

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) :	STEL (EC)
Limit value :	150 ppm / 723 mg/m^3
Version :	20.06.2019
Limit value type (country of origin) :	TWA (EC)
Limit value :	50 ppm / 241 mg/m^3
Version :	20.06.2019

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable material : Butyl caoutchouc (butyl rubber)

Required properties : liquid-tight.

Breakthrough time : > 10 min See information supplied by the manufacturer.

Thickness of the glove material : 0,5mm

Recommended glove articles : When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Additional hand protection measures : Check leak tightness/impermeability prior to use. Do not wear gloves near rotary machines and tools. Take recovery periods for skin regeneration. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Remark : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Required properties : antistatic.

Recommended material : Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter: A

Consumer exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Aerosol

Colour : please refer to label

Odour

like: Solvents/Thinner

Safety characteristics

Initial boiling point and boiling range :	(1013 hPa)	<	35	°C	
Flash point :		<	1	°C	
Lower explosion limit :			0,7	Vol-%	
Upper explosion limit :			32	Vol-%	
Density :	(20 °C)	approx.	0,8	g/cm³	
Flow time :	(20 °C)		not applicable		DIN-cup 4 mm

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions(See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours. Exothermal decomposition with formation of: Carbon dioxide. Carbon monoxide Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

There are no data available on the preparation/mixture itself. Classification according to Regulation (EC) No 1272/2008 [CLP] See Sections 2 and 3 for details.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Acute toxicity No information available.

Corrosion

Skin corrosion/irritation Serious eye damage/eye irritation No information available.

Respiratory or skin sensitisation

Respiratory or skin sensitisation No information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No information available.

Germ cell mutagenicity

No information available.

Reproductive toxicity

No information available.

STOT-single exposure

No information available.

STOT-repeated exposure

No information available.

Aspiration hazard

No information available.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

There are no data available on the preparation/mixture itself. Do not allow to enter into surface water or drains.

12.1 Toxicity

No information available.

12.2 Persistence and degradability
No information available.

12.3 Bioaccumulative potential
No information available.

12.4 Mobility in soil
No information available.

12.5 Results of PBT and vPvB assessment
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties
No information available.

12.7 Other adverse effects
No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Do not allow to enter into surface water or drains. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Directive 2008/98/EC (Waste Framework Directive)
Before intended use

Waste codes/waste designations according to EWC/AVV

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

After intended use

Waste codes/waste designations according to EWC/AVV

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

Other disposal recommendations

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

SECTION 14: Transport information

14.1 UN number or ID number
UN 1950

14.2 UN proper shipping name
Land transport (ADR/RID)

AEROSOLS

Sea transport (IMDG)

AEROSOLS

Air transport (ICAO-TI / IATA-DGR)

AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)
Land transport (ADR/RID)

Class(es) :	2
Classification code :	5F
Hazard identification number (Kemler No.) :	23
Tunnel restriction code :	D
Special Provisions :	LQ 1 l · E 0

Hazard label(s) : 2.1

Sea transport (IMDG)

Class(es) : 2.1
EmS-No. : F-D / S-U
Special Provisions : LQ 1 l · E 0
Hazard label(s) : 2.1

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 2.1
Special Provisions : E 0
Hazard label(s) : 2.1

14.4 Packing group

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40, 48, 75

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

15. Restrictions on use

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

EUH066	Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

None

16.7 Additional information

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.